Chair Armrest Durability Testing Machine

This machine is used to test durability of frame of chair armrest.

| Model | QRCAD-203 |
|-------------------------|--------------------------------------|
| Max. Load Capacity (kN) | 2 |
| Min. Load Capacity (N) | 0.04 |
| Accuracy | Within ± 0.5 % of the indicated load |
| Operation Type | Servo motor |
| Test Speed | 1 ~ 40 000 mm/min |
| Test Control | Load, stroke |
| Load Sensor | Load cell |
| Test Speed Control | Manual, computer |
| Safety Device | Micro limit switch |
| Load Dimension (mm) | 1800 × 1200 × 2100 |
| Power | 1P, AC 220 V, 60 Hz |
| Power Consumption (kW) | |
| Weight (kg) | 400 |



Chair Tilt Durability Testing Machine

This machine is used to test durability of tilt and back and frame of chair.





| Model | QRCTD-203 |
|-------------------------|--------------------------------------|
| Max. Load Capacity (kN) | 5 |
| Min. Load Capacity (N) | 0.1 |
| Accuracy | Within ± 0.5 % of the indicated load |
| Operation Type | Servo motor |
| Test Speed | 1 ~ 32 000 mm/min |
| Test Control | Load, stroke |
| Load Sensor | Load cell |
| Test Speed Control | Manual, computer |
| Safety Device | Micro limit switch |
| Load Dimension (mm) | 1 800 × 1 200 × 2 100 |
| Power | 1P, AC 220 V, 60 Hz |
| Power Consumption (kW) | 1.5 |
| Weight (kg) | 400 |

