

Natural Convection Oven

This chamber is used to test glass, specimen and heat curing.



Model	QRNCO-742	QRNCO-781	QRNCO-7150	QRNCO-7300	QRNCO-7630	QRNCO-71152
Temperature	Max. 250 °C					
Control	Digital PID controller					
Internal Dimensions	350 × 350 × 350	450 × 400 × 450	600 × 500 × 500	600 × 500 × 1 000	900 × 700 × 1 000	1 200 × 800 × 1 200
External Dimensions	520 × 525 × 770	620 × 575 × 870	770 × 675 × 920	770 × 675 × 1 550	1 200 × 850 × 1 550	1 550 × 1 100 × 1 800
Internal Material	SUS 304 polished					
External Material	Powder coating					
Insulation	Ceramic wool+ glass wool					
Door Packing	High Temp. grade foamed silicone rubber					
Windows	Tempered safety glass, three fold					
Safety Device	Over Temp. limit					
Power (kW)	220 V, 0.8	220 V, 1.2	220 V, 1.5	220 V, 2.5	220 V, 6	3P, 220 V, 10

Forced Convection Oven

This chamber is used to test glass, specimen and heat curing.



Model	QRFCO-742	QRFCO-781	QRFCO-7150	QRFCO-7150	QRFCO-7630	QRFCO-7300
Temperature	Max. 250 °C					
Control	Digital PID controller					
Internal Dimensions	350 × 350 × 350	450 × 400 × 450	600 × 500 × 500	600 × 500 × 1 000	900 × 700 × 1 000	1 200 × 800 × 1 200
External Dimensions	520 × 525 × 770	620 × 575 × 870	770 × 675 × 920	770 × 675 × 1 550	1 200 × 850 × 1 550	1 550 × 1 100 × 1 800
Internal Material	SUS 304 polished					
External Material	Powder coating					
Insulation	Ceramic wool + glass wool					
Door Packing	High Temp. grade foamed silicone rubber					
Windows	Tempered safety glass, three fold					
Safety Device	Over Temp. limit					
Power (kW)	220 V, 0.8	220 V, 1.2	220 V, 1.5	220 V, 1.5	220 V, 6	220 V, 2.5